

## MARSHALL MULTISPREAD

### SPECIFICATION SHEET 2010

MODEL	825T	825T-HS	845T-L	860T-L	880T	810T	850TM	880TM	810TM	945T-L	960T-L	980T	910T	950TM	980TM	910TM	9140	9160
Length (overall)	4350	4350	5050	5050	5660	5660	4200	4780	4780	5050	5050	5660	5660	4200	4780	4780	7215	7215
Width (hopper top)	1900	1600	2200	2200	2300	2300	2300	2300	2300	2200	2200	2300	2300	2300	2300	2300	2500	2500
Width overall	2170	1900	2470	2500	2730	2730	2300	2300	2300	2470	2500	2730	2730	2300	2300	2300	2730	3000
Length (hopper top)	2440	2215	3000	3000	3600	3600	3000	3600	3600	3000	3000	3600	3600	3000	3600	3600	5000	5000
Height (overall)	1640	1650	1815	2070	2330	2530	1180	1400	1600	1815	2070	2330	2530	1180	1400	1600	2475	2710
Track	1750	1620	1960	1950	2150	2150	N/A	N/A	N/A	1960	1950	2150	2150	N/A	N/A	N/A	2150	2430
Nett weight	1080	1100	1550	1670	2200	2290	1325	1460	1550	1550	1670	2250	2500	1325	1460	1550	4600	4750
Load capacity nominal	2500kg	2500kg	4500kg	6000kg	8000kg	10,000kg	5000kg	8000kg	10,000kg	4500kg	6000kg	8000kg	10,000kg	5000kg	8000kg	10,000kg	14,000kg	16,000kg
Hopper cubic capacity	2.2m <sup>3</sup>	2.0m <sup>3</sup>	3.8m <sup>3</sup>	5.1m <sup>3</sup>	6.5m <sup>3</sup>	8.1m <sup>3</sup>	4.1m <sup>3</sup>	6.5m <sup>3</sup>	8.1m <sup>3</sup>	3.8m <sup>3</sup>	5.1m <sup>3</sup>	6.5m <sup>3</sup>	8.1m <sup>3</sup>	4.1m <sup>3</sup>	6.5m <sup>3</sup>	8.1m <sup>3</sup>	10.6m <sup>3</sup>	12.5m <sup>3</sup>
Discharge capacity per ha	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg	25 to 8000kg
Tyres	400/60 x 15.5	1100 x 16	500/60 x 22.5	550/60 x 22.5	23.1 x 26	23.1 x 26	N/A	N/A	N/A	500/60 X 22.5	550/60 X 22.5	23.1 X 26	23.1 X 26	N/A	N/A	N/A	550/60 X 22.5	600/55 X 26
Operating work speed	Up to 25km/hr	Up to 25km/hr	Up to 25km/hr	Up to 25km/hr	Up to 25km/hr	Up to 25km/hr	Up to 40km/hr	Up to 40km/hr	Up to 40km/hr	Up to 25km/hr	Up to 25km/hr	Up to 25km/hr	Up to 25km/hr	Up to 25km/hr	Up to 40km/hr	Up to 40km/hr	Up to 25km/hr	Up to 25km/hr
Highway travel speed	80km/hr	80km/hr	80km/hr	80km/hr	80km/hr	80km/hr	100km/hr	100km/hr	100km/hr	80km/hr	80km/hr	80km/hr	80km/hr	100km/hr	100km/hr	100km/hr	80km/hr	80km/hr
Spinner size	600mm	600mm	600mm	600mm	600mm	600mm	600mm	600mm	600mm	700mm	700mm	700mm	700mm	700mm	700mm	700mm	700mm	700mm
Spreading width	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 36m	Up to 36m	Up to 36m	Up to 36m	Up to 36m	Up to 36m	Up to 36m	Up to 36m	Up to 36m
Ground wheel drive	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
Power required	PTO	Hyd	PTO	PTO	PTO	PTO	20hp	20hp	20hp	Hyd	Hyd	Hyd	Hyd	25hp	25hp	25hp	Hyd	Hyd

